



Illinois Wesleyan University
Digital Commons @ IWU

John Wesley Powell Student Research
Conference

1993, 4th Annual JWP Conference

May 8th, 9:30 AM - 4:30 PM

A Novel Technique for Studying the Shear Elastic Response of Weak Solids

Jason A. Payne
Illinois Wesleyan University

Narendra Jaggi, Faculty Advisor
Illinois Wesleyan University

Follow this and additional works at: <https://digitalcommons.iwu.edu/jwprc>

Payne, Jason A. and Jaggi, Faculty Advisor, Narendra, "A Novel Technique for Studying the Shear Elastic Response of Weak Solids" (1993). *John Wesley Powell Student Research Conference*. 17.

<https://digitalcommons.iwu.edu/jwprc/1993/posters/17>

This Event is protected by copyright and/or related rights. It has been brought to you by Digital Commons @ IWU with permission from the rights-holder(s). You are free to use this material in any way that is permitted by the copyright and related rights legislation that applies to your use. For other uses you need to obtain permission from the rights-holder(s) directly, unless additional rights are indicated by a Creative Commons license in the record and/ or on the work itself. This material has been accepted for inclusion by faculty at Illinois Wesleyan University. For more information, please contact digitalcommons@iwu.edu.

©Copyright is owned by the author of this document.

A NOVEL TECHNIQUE FOR STUDYING THE SHEAR ELASTIC RESPONSE OF WEAK SOLIDS

Jason A. Payne, Department of Physics, IWU, Narendra Jaggi*

Traditionally, the shear elastic properties of solids have been measured using mechanical instrumentation, i.e. springs and balances. Commercially available instruments are designed to study engineering materials (steel for example) and are not useful for investigating weak solids, such as gels and electrorheological fluids. We have developed a simple, inexpensive, and precise technique to measure the shear elastic modulus of weak solids using electromagnetic and optical tools. This technique can easily be adapted to measure the viscosity of a liquid also. A Helmholtz pair was used to produce a torque on a permanent magnet mounted on the smaller of two concentric cylinders, coupled by the material to be studied. The torque was controlled precisely and measured accurately in terms of the current flowing through the coils of the Helmholtz pair. An optical lever was employed to measure the angular displacement of the inner cylinder as a function of the applied shear stress. The instrument has been validated by making measurements on lemon jello, and agarose gels of varying concentrations. The technique has also been applied to the study of electric field induced "freezing" of electrorheological fluids, a subject of enormous contemporary interest.

[This work is supported by a NASA/JOVE grant to the Illinois Wesleyan University Physics Department]