



Apr 17th, 9:00 AM - 10:00 AM

Adaptive Optics for Dynamic Optical Traps

Olukayode Karunwi
Illinois Wesleyan University

Ryan Smith
Illinois Wesleyan University

Gabriel Spalding, Faculty Advisor
Illinois Wesleyan University

Follow this and additional works at: <https://digitalcommons.iwu.edu/jwprc>

Karunwi, Olukayode; Smith, Ryan; and Spalding, Faculty Advisor, Gabriel, "Adaptive Optics for Dynamic Optical Traps" (2004). *John Wesley Powell Student Research Conference*. 16. <https://digitalcommons.iwu.edu/jwprc/2004/posters/16>

This is protected by copyright and/or related rights. It has been brought to you by Digital Commons @ IWU with permission from the rights-holder(s). You are free to use this material in any way that is permitted by the copyright and related rights legislation that applies to your use. For other uses you need to obtain permission from the rights-holder(s) directly, unless additional rights are indicated by a Creative Commons license in the record and/ or on the work itself. This material has been accepted for inclusion by faculty at Illinois Wesleyan University. For more information, please contact digitalcommons@iwu.edu.

©Copyright is owned by the author of this document.

Poster Presentation P25

ADAPTIVE OPTICS FOR DYNAMIC OPTICAL TRAPS

Olukayode Karunwi, Ryan Smith and Gabriel Spalding*
Department of Physics, Illinois Wesleyan University

Holographic Optical Tweezers were first demonstrated by Fournier, *et al*¹, using a commercial hologram. A complete recipe for making *tailored*, planar arrays of optical traps using Diffractive Optical Elements (DOE) was laid out in the IWU – Univ. of Chicago collaboration, “Computer-Generated Holographic Optical Tweezer Arrays.”² While this original “HOT” recipe dealt with two-dimensional arrays, several generalizations have been demonstrated which extend the basic method to three-dimensions^{3, 4}. That said, three-dimensional studies remain in their infancy. Furthermore, even for lower-dimensional arrays, both errors in the DOE and aberrations in the optical system can compromise trap performance. We will report on our progress in using a Programmable Phase Modulator (an optically addressable DOE) to provide a reconfigurable, self-calibrating DOE, and to correct for aberrations. Our approach involves modifying the “HOT” algorithm in order to provide a feedback mechanism between the input optical array and output optical array.

- ¹ J.-M. R. Fournier, M. M. Burns, and J. A. Golovchenko, Proceedings SPIE — The International Society for Optical Engineering **2406**, 101 (1995).
- ² E. R. Dufresne, G. C. Spalding, M. T. Dearing, et al., Review of Scientific Instruments **72**, 1810 (2001).
- ³ H. Melville, G. F. Milne, G. C. Spalding, et al., Optics Express (2003).
- ⁴ J. Leach, G. Sinclair, P. Jordan, et al., Optics Express **12**, 220 (2004).