



Illinois Wesleyan University
Digital Commons @ IWU

John Wesley Powell Student Research
Conference

2007, 18th Annual JWP Conference

Apr 14th, 11:00 AM - 12:00 PM

Rapid Object Detection Using Independent Component Analysis

Aditya Rajgarhia
Illinois Wesleyan University

Weiyu Zhu, Faculty Advisor
Illinois Wesleyan University

Follow this and additional works at: <https://digitalcommons.iwu.edu/jwprc>

Rajgarhia, Aditya and Zhu, Faculty Advisor, Weiyu, "Rapid Object Detection Using Independent Component Analysis" (2007). *John Wesley Powell Student Research Conference*. 2.

<https://digitalcommons.iwu.edu/jwprc/2007/oralpres12/2>

This Event is protected by copyright and/or related rights. It has been brought to you by Digital Commons @ IWU with permission from the rights-holder(s). You are free to use this material in any way that is permitted by the copyright and related rights legislation that applies to your use. For other uses you need to obtain permission from the rights-holder(s) directly, unless additional rights are indicated by a Creative Commons license in the record and/ or on the work itself. This material has been accepted for inclusion by faculty at Illinois Wesleyan University. For more information, please contact digitalcommons@iwu.edu.

©Copyright is owned by the author of this document.

Oral Presentation O12.2

RAPID OBJECT DETECTION USING INDEPENDENT COMPONENT ANALYSIS

Aditya Rajgarhia and Weiyu Zhu*

Computer Science Department, Illinois Wesleyan University

Face detection is the task of determining the locations and sizes of human faces in arbitrary digital images. A commonly used approach is based on the techniques of boosting and cascading, which allows for real-time face detection. However, systems based on boosted cascades have been shown to suffer from low detection rates in the later stages of the cascade. In this paper we introduce a novel variation of the boosting process that uses features extracted by Independent Component Analysis (ICA), which is a statistical technique that reveals the hidden factors that underlie sets of random variables or signals. The information describing a face may be contained in both linear as well as high-order dependencies among the image pixels. These high-order dependencies can be captured effectively by representation in ICA space. Moreover, it has been argued that the metric induced by ICA is superior to other methods in the sense that it may provide a representation that is more robust to the effect of noise such as variations in lightening. We propose that features extracted from such a representation may be boosted better in the later stages of the cascade, thus leading to improved detection rates while maintaining comparable speed. We present the results of our face detector, as well as comparisons with existing systems.